**PAGE:** 1 of 3

**PRINT DATE:** 31/07/2002

# SAFETY DATA SHEET

**REF**: M27

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product name: Tuftec - Base

**Supplier:** MMP-International, Division

of ITW Ltd.

Brunel Close, Park Farm

Ind Est,

Wellingborough, Northants,

NN8 6QX

**Emergency telephone number:** +44 (0) 1933 670870 **Fax No:** +44 (0) 1933 670800

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Identification of the preparation

Chemical Name	CAS-No EEC-No	Class	Weight %
Bisphenol A/F Epoxy Resin	40216-08- 8	Xi; R36/38, R43	30-60
Hexanediol Diglycidyl Ether	16096-31- 4	Xi; R36/38, R43	5-15
C13/15 Glycidyl Ether	68081-84- 5	Xi; R36/38, R43	5-15

#### 3. HAZARDS IDENTIFICATION

Most important hazards: Irritating to eyes and skin.

**Specific hazards** May cause sensitisation by skin contact.

## 4. FIRST AID MEASURES

**General advice:** Show this safety data sheet to the doctor in attendance. Avoid contact with skin

and eyes.

**Inhalation:** Move to fresh air. Consult a physician after significant exposure.

Skin contact: Remove immediately adhering matter, Wash off immediately with soap and

plenty of water. If skin irritation persists, call a physician.

**Eye contact:** In the case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

Ingestion: Rinse mouth, Do not induce vomiting, Call a physician immediately. If a person

vomits when lying on their back, place them in the recovery position.

# 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media:** dry powder, foam, carbon dioxide (CO2) **Extinguishing media which must not be used for safety reasons:** 

high volume water jet.

**Specific hazards:** Burning produces irritant fumes.

**Special protective equipment for firefighters:** In the event of fire, wear self contained

breathing apparatus, protective suit

**Specific methods:** Standard procedure for chemical fires

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Avoid contact with the skin and the eyes. Use personal protective

equipment. Ensure adequate ventilation.

**Environmental precautions:** Do not contaminate water. Avoid subsoil penetration.

Methods for cleaning up: Dam up, Scrape-up, Soak up with inert absorbent material, Transfer

to covered steel drums.

**PAGE:** 2 of 3

Product name: Tuftec - Base PRINT DATE: 31/07/2002

**REF:** M27

#### 7. HANDLING AND STORAGE

**Handling:** Use only in well-ventilated areas. Keep away from heat and sources of ignition.

General industrial hygiene practice.

**Storage:** Keep containers tightly closed in a cool, well-ventilated place.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Chemical Name: National occupational exposure limits

(British COSHH - EH40):

Bisphenol A/F Epoxy Resin Hexanediol Diglycidyl Ether C13/15 Glycidyl Ether

Engineering measures

- Respiratory protection: No personal respiratory protective equipment normally required. In

case of insufficient ventilation, wear suitable respiratory equipment.

Hand protection: solvent-resistant gloves (butylrubber)
Eye protection: safety glasses with side-shields, goggles.

- **Skin and body protection:** Wear as appropriate.

**Hygiene measures:** Wash hands before breaks and immediately after handling the

product, Keep away from food, drink and animal feeding stuffs. Do

not smoke. General industrial hygiene practice.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid Colour: Odour: mild

g/I H2O)

**Boiling point/range:** >200 °C **Flash point:** >150 °C

Vapour pressure: <0.001Pa mm Hg ( 20 °C)

## 10. STABILITY AND REACTIVITY

Stability: Stable

**Conditions to avoid:** Prolonged heating at temperatures above .?

Materials to avoid: strong acids and strong bases, and oxidizing agents (strong)

**Hazardous decomposition products:** carbon oxides, aldehydes.

## 11. TOXICOLOGICAL INFORMATION

**Acute toxicity:** Epoxy constituents: LD50/oral/rat = 30g/Kg

LD50/dermal/rabbit = > 20 ml/Kg LC50/inhalation/4h/rat = fatality = 0

**Local effects:** Moderate skin irritation

**Sensitization:** May cause sensitisation by skin contact.

**Long term toxicity:** Components of the product may be absorbed into the body by inhalation and

ingestion.. Repeated or prolonged skin contact may cause allergic reactions

with susceptible persons.

### 12. ECOLOGICAL INFORMATION

**Mobility:** Do not contaminate water. Do not let product enter drains.

#### 13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products: Solidify unexposed surplus and dispose of together

with processed material as cured plastic waste - In accordance with local and national regulations

Contaminated packaging: In accordance with local and national regulations

**European waste Catalogue No:** 08 04 99

Product name: Tuftec - Base

**PAGE:** 3 of 3

**PRINT DATE:** 31/07/2002

**REF:** M27

# 14. TRANSPORT INFORMATION

**Proper shipping name:** Not classified as dangerous in the meaning of transport

regulations: UN, ADR/RID, IMO & IATA/ICAO.

#### 15. REGULATORY INFORMATION

Classification according to European directive on classification of hazardous preparations 93/21/EEC

- Contains: BISPHENOL A/F EPOXY RESIN

- Symbol(s):



Χi

**R-phrase(s):** R43 - May cause sensitization by skin contact. R36 - Irritating to eyes. R38 -

Irritating to skin.

S-phrase(s): S28 - After contact with skin, wash immediately with plenty of water. S37/39 - Wear

suitable gloves and eye/face protection.

# **16. OTHER INFORMATION**

Recommended use: Adhesives.

**Recommended restrictions:** 

When used in a mixture, read the labels and safety data sheets of all components.

**Revision date:** 15/07/2002

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication