SAFETY DATA SHEET

PAGE: 1 of 3 PRINT DATE: 02/08/2002

REF: R16

Product name:					MPANY/UNDERTAKING	3	
Supplier:	Repairite Liquid Metal Activator MMP-International, Division						
Suppliel.			MMP-International, Division of ITW Ltd.				
			se, Park Farm				
		Ind Est, Wellingbor	ough Northan	its			
		Wellingborough, Northants, NN8 6QX					
Emergency telepho	one number:	+44 (0) 19	33 670870				
Fax No:		+44 (0) 19	33 670800				
2. COMPOSITION/INF	ORMATION	ON INGREDIE	ENTS				
Identification of the	e preparatio	on					
Chemical Name			CAS-No	EEC-No	Class	Weight 9	
BENZYL ALCOHOL			100-51-6	603-057- 00-5	Xn; R20/22	10-15	
DIETHYLENETRIAMINE			111-40-0	612-058- 00-X	Xn; R21/22 C; R34 R43	1-5	
3. HAZARDS IDENTIF							
Most important ha	-	in irritation, Eye i	irritation. Caus	ses sensitizatio	٦.		
Specific hazards		-			ion by skin contact.		
4. FIRST AID MEASU					, ,		
General advice:		fety data sheet to	the doctor in	attendance.			
Inhalation:	Move to fresh	-					
Skin contact:	Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician.						
Eye contact:	liately with plenty	of water and	seek medical a	dvice.			
Ingestion:	Drink plenty	of water. Call a	physician imm	nediately.			
5. FIRE-FIGHTING ME	EASURES						
Suitable extinguish	ing media:	Carbon Dioxid	de (CO 2),	Water spray, dr	y chemical, foam.		
Specific hazards:		re and/or explosion		the fumes.			
Special protective	equipment f	for firefighter			ar a self contained breathing		
				paratus, wear p uipment.	personal protective		
Specific methods:	Standard	procedure for ch	'				
6. ACCIDENTAL RELE	ASE MEASL	JRES					
Personal precautions: Ave			ith skin and ey	yes. Use persor	al protective equipment.		
		Ensure adequat	e ventilation.				
Environmental precautions: Do n		Do not let produ	o not let product enter drains.				
Methods for cleani	ng up:	Soak up with ine for disposal.	ert absorbent	material. Shove	I into suitable container		
7. HANDLING AND S	TORAGE						
		II-ventilated areas	s. Avoid conta	ct with skin, eye	es and clothing.		

Product name:

Repairite Liquid Metal Activator

BENZYL ALCOHOL					
DIETHYLENETRIAMINE	4.3mg/m3				
Engineering measures to reduce exposure	Ensure adequate ventilation, especially in confined areas. No personal respiratory protective equipment normally required, In case of insufficient ventilation wear suitable respiratory equipment. PVC or other plastic material gloves. safety glasses with side-shields. Wear as appropriate. Wash hands before breaks and immediately after handling the product. Keep away from food, drink and animal feeding stuffs. Do not smoke. General industrial hygiene practice.				
- Respiratory protection:					
- Hand protection:					
- Eye protection:					
- Skin and body protection:					
Hygiene measures:					
9. PHYSICAL AND CHEMICAL PRO					
Form: liquid	Colour: black Odour: slight				
g/I H2O)					
Boiling point/range:	>200 °C				
Flash point:	>100 °C				
Melting point/range:	n/d °C				
Flammability (solid, gas):	Will burn if involved in a fire.				
Relative density:	- lower 2.00g/cm3 (20 °C)				
10. STABILITY AND REACTIVITY					
Stability: Stable					
Materials to avoid: oxidizin	ing agents, acids.				
Hazardous decomposition produ	ucts: Carbon monoxide, Carbon Dioxide (CO 2), nitrogen oxides (NOx), Ammonia.				
11. TOXICOLOGICAL INFORMATIO)N				
Acute toxicity: LD50/oral/	/rat = n/d				
12. ECOLOGICAL INFORMATION					
Mobility:	Do not let product enter drains.				
Other information:	Water hazard class - 1 slightly water contaminating				
13. DISPOSAL CONSIDERATIONS					
Waste from residues / unused p	products: Solidify unexposed surplus and dispose of together with processed material as cured plastic waste.				
Contaminated packaging:	In accordance with local and national regulations				
European waste Catalogue No:	08 04 99				
14. TRANSPORT INFORMATION					
Proper shipping name:	Not classified as dangerous in the meaning of transport regulations: UN, ADR/RID, IMO & IATA/ICAO.				
15. REGULATORY INFORMATION	opean directive on classification of hazardous preparations				

Classification according to European directive on classification of hazardous preparations 93/21/EEC

- Contains: DIETHYLENETRIAMINE, BENZYL ALCOHOL

Product name:	Depaining Liquid Matel	PAGE: 3 of 3 PRINT DATE: 02/08/2002 REF: R16			
found fidline.	Repairite Liquid Metal				
	Activator				
- Symbol(s):	×				
	Xi - Irritant				
R -phrase(s):	R36/38 - Irritating to eyes and skin. R43 - May cause sensitization by skin contact.				
S -phrase(s):	S24 - Avoid contact with skin S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.S28 - After contact with skin, wash immediately with plenty of soapy water. S36/37/39 - Wear suitable protective clothing, gloves and eye/face protection.				
16. OTHER INFOR	RMATION				
Recommended	use:				
Recommended	restrictions:				
When used in a mix	tture, read the labels and safety data sheets of all compor	nents.			
Revision date:	16/07/2002				

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication