PAGE: 1 of 3

PRINT DATE: 07/02/2003 SAFETY DATA SHEET

**REF: R44** 

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

REPAIRITE LIQUID RUBBER PUTTY Product name:

HARDENER

Supplier: MMP-International, Division

of ITW Ltd.

Brunel Close, Park Farm Ind

Wellingborough, Northants,

NN8 6QX

Emergency telephone number: +44 (0) 1933 670870 Fax No: +44 (0) 1933 670800

2. COMPOSITION/INFORMATION ON INGREDIENTS

Identification of the preparation

Chemical Name CAS-No EEC-No Class Weight %

DIETHYLTOLUENEDIAMINE 68479-98-1 Xn; R21/22 R48 20-50

3. HAZARDS IDENTIFICATION

Most important hazards: Irritating to eyes and skin. Specific hazards Harmful in contact with skin.

4. FIRST AID MEASURES

General advice: Show this safety data sheet to the doctor in attendance. Avoid contact with skin and

eyes.

Inhalation: Move to fresh air, Consult a physician if necessary. Skin contact: Wash off immediately with soap and plenty of water.

Eye contact: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Ingestion: Drink plenty of water, Induce vomiting immediately and call a physician. If a person

vomits when lying on his back, turn over on his side.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: foam, dry powder, Carbon Dioxide (CO<sub>2</sub>).

Extinguishing media which must not be used for safety reasons:

water

Specific hazards: Burning produces irritant fumes.

Special protective equipment for firefighters: In case of fire, wear a self contained breathing

apparatus, protective suit.

Specific methods: Standard procedure for chemical fires.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Avoid contact with skin and eyes, Inhalation.

Environmental precautions: Do not let product enter drains

Methods for cleaning up: Soak up with inert absorbent material, Shovel into a dry metal container.

7. HANDLING AND STORAGE

Handling: Avoid contact with skin and eyes. Open drum carefully as content may be under

pressure. Use only in well-ventilated areas.

Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources Storage:

of ignition - No smoking

PAGE: 2 of 3

Product name: REPAIRITE LIQUID PRINT

RUBBER PUTTY

PRINT DATE: 07/02/2003

**REF: R44** 

HARDENER

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Chemical Name: National occupational exposure limits:

DIETHYLTOLUENEDIAMINE no data available

Engineering measures to

Respiratory protection:

Ensure adequate ventilation, especially in confined areas.

reduce exposure

Not required with adequate ventilation. If the product is heated, wear

approved organic vapor respirator.

Hand protection: nitrile rubber and Neoprene gloves.
 Eye protection: safety glasses with side-shields.

- Skin and body protection: protective suit , safety shoes.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. Do not smoke.

General industrial hygiene practice

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: liquid. Colour: black. Odour: pungent.

pH: ( 50 g/l H2O) >7 (20 °C) Boiling point/range: >100 °C Flash point: >135 °C

Relative density: - lower 1.05 ( 20 °C)

Water solubility partly soluble

10. STABILITY AND REACTIVITY

Stability: Stable.

Conditions to avoid: temperatures above 50 °C.

Materials to avoid: strong acids and oxidizing agents.

Hazardous decomposition products: Carbon monoxide nitrogen oxides (NOx).

11. TOXICOLOGICAL INFORMATION

Acute toxicity: LD50/oral/rat = >500 mg/kg LD50/dermal/rat = >1000 mg/kg Local effects: The product causes irritation of eyes, skin and mucous membranes.

12. ECOLOGICAL INFORMATION

Mobility: Do not contaminate water.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products: Solidify unexposed surplus and dispose of together with

processed material as cured plastic waste - In accordance with local and national regulations

Contaminated packaging: In accordance with local and national regulations.

European waste Catalogue No: 08 04 99

14. TRANSPORT INFORMATION

Proper shipping name: Not classified as dangerous in the meaning of transport regulations:

UN, ADR/RID, IMO & IATA/ICAO.

15. REGULATORY INFORMATION

Classification according to European directive on classification of hazardous preparations 93/21/EEC

- Contains: **DIETHYLTOLUENEDIAMINE** 

Product name:

## REPAIRITE LIQUID RUBBER PUTTY HARDENER

PAGE: 3 of 3

PRINT DATE: 07/02/2003

REF: **R44** 

- Symbol(s):



Xn - Harmful.

R -phrase(s): R36 - Irritating to eyes. R21/22 - Also harmful in contact with skin and if swallowed

R48 - Danger of serious damage to health by prolonged exposure.

S -phrase(s): S26 - In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice. S28 - After contact with skin, wash immediately with plenty of water.

S36/37/39 - Wear suitable protective clothing, gloves and eye/face protection.

## 16. OTHER INFORMATION

Recommended use: Adhesives.

Recommended restrictions:

When used in a mixture, read the labels and safety data sheets of all components. All metal parts of the mixing and processing equipment must be earthed.

Revision date: 10/12/2002

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication