## SAFETY DATA SHEET

PAGE: 1 of 3 PRINT DATE: 02/08/2002

**REF:** R21

Product name: Supplier: Emergency telephone number: Fax No:		Repa	Repairite Release Agent							
			MMP-International, Division of ITW Ltd.							
		Brunel (	Brunel Close, Park Farm Ind Est,							
		Wellingborough, Northants, NN8 6QX								
		+44 (0)	+44 (0) 1933 670870 +44 (0) 1933 670800							
		+44 (0)								
. COMPOSITION/INF	ORMATIO	N ON INGREE	DIENTS							
Identification of the	e preparat	ion								
Chemical Name			CAS-No	EEC-No	Class	Weight				
BUTANE			106-97-8	601-004- 00-0	F+; R12	10-30				
PROPANE			74-98-6	601-003- 00-5	F+; R12	10-30				
HEPTANE			142-82-5	601-008- 00-2	F; R11	5-10				
. HAZARDS IDENTIF	ICATION									
Most important haz	ards:	Extremely flamm	able.							
. FIRST AID MEASUF	RES									
Inhalation:	Move to fresh air, Consult a physician after significant exposure.									
Skin contact:	Remove immediately adhering matter. Wash off immediately with soap and plenty of water, If skin irritation persists, call a physician.									
Eye contact:	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.									
Ingestion:	Call a phys	ician immediate	ly, Do not induce	vomiting.						
. FIRE-FIGHTING ME	ASURES									
Suitable extinguish	ing media	alcohol-res spray.	istant foam, Carl	oon Dioxide (CC	) <sub>2</sub> ), dry pow	vder, Water				
Specific hazards:			osion do not brea							
Special protective	pecial protective equipment for f			firefighters: In case of fire, wear a self contained breathing apparatus, protective suit.						
. ACCIDENTAL RELE		SURES								
Personal precaution			h vapours or spra	-						
-		-	o not let product enter drains.							
Methods for cleani	ng up:		and, silica gel, acid to covered steel drum	IS.						
. HANDLING AND ST	ORAGE									
Handling:	Use only in well-ventilated areas. Keep away from heat and sources of ignition.									
Storage:	Keep containers tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking.									
. EXPOSURE CONTR	ROLS / PE	RSONAL PRO	TECTION							

PAGE: 2 of 3 PRINT DATE: 02/08/2002 REF: R21

BUTANE		1450mg/m3						
PROPANE		Asphyxiant						
HEPTANE		500ppm						
Engineering measures to reduce exposure		Ensure adequate ventilation, especially in confined areas						
- Respiratory protection:		Breathing apparatus with filter.						
- Hand protection:		gloves 9 (Advice should be sought on the type of gloves).						
- Eye protection:		safety glasses.						
- Skin and body protection:		protective suit.						
Hygiene measures:								
9. PHYSICAL AND CHEMICAL PROPERTIES								
Form: oily - aerosol		Colour:	colourless.		Odour:	hydrocarbon-like		
<b>pH:</b> g/l ⊦	120)	N/A						
Boiling point/range:		71	°C					
Flash point:		-40	°C					
Melting point/range:		<0	°C					
Autoignition temperature:		>230	°C					
Explosive properties:		None						
Explosion limits:		- lower	0.8	vol. % -	upper 9.	0 vol. %		
Oxidizing properties:		None						
Vapour pressure:		2.75 Bar						
Water solubility		insoluble						
10. STABILITY AND REA	СТІVІТҮ							
Stability:	Stable							
Conditions to avoid:	Keep away from heat and sources of ignition.							
Materials to avoid:	oxidizinę	g agents, stro	ng acids, strong	g bases.				
Hazardous decompos	ition produ		Carbon monoxic NOx).	de, Carbon Diox	kide (CO	2), nitrogen oxides		
11. TOXICOLOGICAL IN	FORMATION	N						
Acute toxicity:	Components of the product may be absorbed into the body by inhalation, ingestion and through the skin. Aliphatic Hydrocarbon Solvent Blend: LD50/oral/rat = >5g/kg							
Local effects:	May be harmful by inhalation, ingestion, skin adsorption. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.							
Sensitization:	May cause skin irritation and/or dermatitis.							
Long term toxicity:	Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.							
Repeated or prolonged exposure: Danger of serious damage to health by prolonged exposure, to the renal / Central nervous system.								
12. ECOLOGICAL INFOR	MATION							
Mobility:	Do not allo	Do not allow material to contaminate ground water system.						
Persistence / degrad	Aquatic tox	Aquatic toxicity is unlikely due to low solubility.						
13. DISPOSAL CONSIDERATIONS								
Wasto from residues		roducte						

Waste from residues / unused products:

PAGE: 3 of 3 PRINT DATE: 02/08/2002

**REF:** R21

Contaminated packaging: Empty containers can be landfilled after cleaning, when in compliance with local regulations. **European waste Catalogue No:** 08 04 99 **14. TRANSPORT INFORMATION** Proper shipping name: Aerosol UN-No: 1950 ADR/RID Class: 2 HI/UN No: 1950 IMO Class: 2 Proper shipping name: Aerosol **ICAO** Class: UN/ID No: 2 1950 Proper shipping name Aerosol **15. REGULATORY INFORMATION** Classification according to European directive on classification of hazardous preparations 93/21/EEC - Contains: PROPANE, BUTANE, HEPTANE. Symbol(s): F+ Extremely flammable R -phrase(s): R12 - Extremely flammable. S -phrase(s): S2 - Keep out of reach of children. S 9 - Keep container in a well-ventilated place. S16 - Keep away from sources of ignition - No smoking.. S23 - Do not breathe vapour. S29 - Do not empty into drains. S33 - Take precautionary measures against static discharges. **16. OTHER INFORMATION Recommended use: Recommended restrictions:** 

When used in a mixture, read the labels and safety data sheets of all components.

**Revision date:** 

01/08/2002

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication