PAGE: 1 of 3 **PRINT DATE:** 31/07/2002

SAFETY DATA SHEET

REF: T1

Product name:	Adhesive	Adhesive				
Supplier:	MMP-International, Division of ITW Ltd.					
	Brunel Close, Park Farm	1				
	Ind Est, Wellingborough, Northants, NN8 6QX					
Emergency telephone number:	+44 (0) 1933 670870					
Fax No:	+44 (0) 1933 670870 +44 (0) 1933 670800					
. COMPOSITION/INFORMATION	ON INGREDIENTS					
Identification of the preparatio	n					
Chemical Name	CAS-No	EEC-No	Class	Weight S		
BUTANONE	78-93-3	606-002- 00-3	F; R11 Xi; R36/37	10-30		
BUTANE	106-97-8	601-004- 00-0	F+; R12	5-10		
HEPTANE	142-82-5	601-008- 00-2	F; R11	10-30		
PROPANE	74-98-6	601-003- 00-5	F+; R12	10-30		
. HAZARDS IDENTIFICATION						
Most important hazards: Ext	remely flammable.					
Specific hazards vap	our, May cause headache and	l dizziness.				
. FIRST AID MEASURES						
	air, Consult a physician after s					
	ediately adhering matter. Wash r, If skin irritation persists, cal		ly with soap and			
	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.					
Ingestion: Call a physici	an immediately, Do not induce	e vomiting.				
. FIRE-FIGHTING MEASURES						
Suitable extinguishing media:	alcohol-resistant foam, Carl spray.	bon Dioxide (CC) ₂), dry powder,	Water		
•	e and/or explosion do not brea	athe fumes.				
Special protective equipment f	•	case of fire, we oparatus, protec	ar a self contained breathi tive suit.	ng		
	procedure for chemical fires.					
Specific methods: Standard						
Specific methods: Standard . ACCIDENTAL RELEASE MEASU	RES					
ACCIDENTAL RELEASE MEASU Personal precautions:	RES Do not breath vapours or spra	ay mist.				
. ACCIDENTAL RELEASE MEASU		5				

Handling: Use only in well-ventilated areas. Keep away from heat and sources of ignition.

roduct name:	Adhesive			AGE: 2 of 3 DATE: 31/07/2002 REF: T1	
Storage:		eep containers tightly closed in a cool, well-ventilated place. Keep away fi ources of ignition - No smoking.			
B. EXPOSURE CON	TROLS / PERSONAL	PROTECTION			
Chemical Name:	National o EH40):	ccupational exposure	e limits (Ref	British COSHH -	
BUTANONE			200ppm		
BUTANE			600ppm		
HEPTANE			500ppm		
PROPANE		no data available			
Engineering mea reduce exposure		ure adequate ventilation, es	specially in confined are	as	
- Respiratory p	rotection: Brea	athing apparatus with filter.			
- Hand protecti	on: glove	es 9 (Advice should be sou	ght on the type of glove	s) .	
- Eye protection	n: safe	ty glasses.			
- Skin and body	y protection: prot	ective suit.			
Hygiene measure	es:				
. PHYSICAL AND (CHEMICAL PROPERTI	ES			
Form: Resin solution		our:	Odour:	hydrocarbon-like	
pH:	g/I H2O) N/A				
Boiling point/ran	5 ,	°C			
Flash point:	-41	°C			
Melting point/rar	nge: <0	°C			
Autoignition tem	-	0°C			
Flammability (sol	-	0.9 (% vol in air at C), UEL 18.6			
Explosive proper	ties: Non	е			
Oxidizing proper	ties: Non	е			
Vapour pressure	3.1	Bar			
Water solubility	inso	luble			
0. STABILITY AND	REACTIVITY				
Stability:	Stable				
Conditions to ave	oid: Keep away fror	m heat and sources of ignit	ion.		
Materials to avoi	id: oxidizing agent	ts, strong acids, strong bas	Ses.		
Hazardous decor	mposition products:	Carbon monoxide, Ca (NOx).	arbon Dioxide (CO	₂), nitrogen oxides	
1. TOXICOLOGICA	L INFORMATION				
Acute toxicity:	Components of the ingestion and throu Aliphatic Hydrocart	Components of the product may be absorbed into the body by inhalation, ingestion and through the skin. Aliphatic Hydrocarbon Solvent Blend: LD50/oral/rat = >5g/kg Butan-2-one: LD50/oral/rat = 3.4g/kg			
Local effects:		May be harmful by inhalation, ingestion, skin adsorption. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.			
		May cause skin irritation and/or dermatitis.			
Sensitization:					

Product name: Adhesiv	PAGE: 3 of 3			
Product name: Adhesive	e PRINT DATE: 31/07/2002			
	REF : T1			
Repeated or prolonged exposu	ure: Danger of serious damage to health by prolonged exposure, to the renal / Central nervous system.			
12. ECOLOGICAL INFORMATION				
Mobility:	Do not allow material to contaminate ground water system.			
Persistence / degradability:	Aquatic toxicity is unlikely due to low solubility.			
13. DISPOSAL CONSIDERATIONS				
Waste from residues / unused	products:			
Contaminated packaging:	Empty containers can be landfilled after cleaning, when in compliance with local regulations.			
European waste Catalogue No:	08 04 00			
14. TRANSPORT INFORMATION				
Proper shipping name:	Aerosol			
UN-No:	1950			
ADR/RID Class:	2			
	HI/UN No: 1950			
IMO Class:	2			
Proper shipping name:	Aerosol			
ICAO Class:	2 UN/ID No: 1950			
Proper shipping name	Aerosol			
15. REGULATORY INFORMATION				
Classification according to Euro 93/21/EEC	opean directive on classification of hazardous preparations			
- Contains: BUTAN	NONE, PROPANE, BUTANE, HEPTANE.			
- Symbol(s):				

Extremely

flammable

S2 - Keep out of reach of children. S 9 - Keep container in a well-ventilated place. S16 - Keep away from sources of ignition - No smoking. S23 - Do not breathe. S25 -Avoid contact with eyes. S29 - Do not empty into drains. S33 - Take precautionary

Xi

16. OTHER INFORMATION

Recommended use:

R -phrase(s):

S -phrase(s):

Recommended restrictions:

When used in a mixture, read the labels and safety data sheets of all components.

measures against static discharges.

Revision date:

09/07/2002

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication

R36/37 - Irritating to eyes and respiratory system.