**PAGE:** 1 of 3

**PRINT DATE:** 31/07/2002

# SAFETY DATA SHEET

**REF:** T17

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product name: Lube 2000

**Supplier:** MMP-International, Division

of ITW Ltd.

Brunel Close, Park Farm

Ind Est,

Wellingborough, Northants,

NN8 6QX

**Emergency telephone number:** +44 (0) 1933 670870 **Fax No:** +44 (0) 1933 670800

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Identification of the preparation

Chemical Name	CAS-No	EEC-No	Class	Weight %
BUTANE	106-97-8	601-004- 00-0	F+; R12	5-10
PROPANE	74-98-6	601-003- 00-5	F+; R12	10-30
HEPTANE	142-82-5	601-008- 00-2	F; R11	5-10

### 3. HAZARDS IDENTIFICATION

Most important hazards: Extremely flammable.

4. FIRST AID MEASURES

**Inhalation:** Move to fresh air, Consult a physician after significant exposure.

**Skin contact:** Remove immediately adhering matter. Wash off immediately with soap and

plenty of water, If skin irritation persists, call a physician.

**Eye contact:** In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

**Ingestion:** Call a physician immediately, Do not induce vomiting.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: alcohol-resistant foam, Carbon Dioxide (CO ,), dry powder, Water

spray.

**Specific hazards:** In case of fire and/or explosion do not breathe fumes.

**Special protective equipment for firefighters:** In case of fire, wear a self contained breathing

apparatus, protective suit.

**6. ACCIDENTAL RELEASE MEASURES** 

**Personal precautions:** Do not breath vapours or spray mist. **Environmental precautions:** Do not let product enter drains.

**Methods for cleaning up:** Soak up with inert absorbent material (e.g. sand, silica gel, acid

binder, universal binder, sawdust). Transfer to covered steel drums.

7. HANDLING AND STORAGE

**Handling:** Use only in well-ventilated areas. Keep away from heat and sources of ignition. **Storage:** Keep containers tightly closed in a cool, well-ventilated place. Keep away from

sources of ignition - No smoking.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Chemical Name: National occupational exposure limits (Ref: British COSHH -

EH40):

**PAGE:** 2 of 3

Product name: Lube 2000

**PRINT DATE:** 31/07/2002

**REF:** T17

BUTANE 600ppm
PROPANE Asphyxiant
HEPTANE 500ppm

**Engineering measures to** 

reduce exposure

Ensure adequate ventilation, especially in confined areas...

- **Respiratory protection:** Breathing apparatus with filter.

- **Hand protection:** gloves 9 (Advice should be sought on the type of gloves) .

Eye protection: safety glasses.Skin and body protection: protective suit.

Hygiene measures:

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Odour: Colour: silver. hydrocarbon-like Form: Aerosol :Ha g/I H2O) N/A Boiling point/range: 71 °C Flash point: -40 °C Melting point/range: °C <0 **Autoignition temperature:** °C >230

Flammability (solid, gas): LEL 0.8 (% vol in air at

25°C), UEL 9.0

Explosive properties: None
Oxidizing properties: None
Vapour pressure: 2.75 Bar
Water solubility insoluble

### 10. STABILITY AND REACTIVITY

Stability: Stable

**Conditions to avoid:** Keep away from heat and sources of ignition. **Materials to avoid:** oxidizing agents, strong acids, strong bases.

**Hazardous decomposition products:** Carbon monoxide, Carbon Dioxide (CO 2), nitrogen oxides

(NOx).

# 11. TOXICOLOGICAL INFORMATION

Acute toxicity: Components of the product may be absorbed into the body by inhalation,

ingestion and through the skin.

Aliphatic Hydrocarbon Solvent Blend: LD50/oral/rat = >5g/kg

Propan-2-ol: LD50/oral/rat = 5.8g/kg

**Local effects:** May be harmful by inhalation, ingestion, skin adsorption. Symptoms of

overexposure may be headache, dizziness, tiredness, nausea and vomiting.

**Sensitization:** May cause skin irritation and/or dermatitis.

Long term toxicity: Repeated or prolonged exposure may cause skin irritation and dermatitis,

due to degreasing properties of the product.

**Repeated or prolonged exposure:** Danger of serious damage to health by prolonged exposure,

to the renal / Central nervous system.

# 12. ECOLOGICAL INFORMATION

Mobility: Do not allow material to contaminate ground water system.

**Persistence / degradability:** Aquatic toxicity is unlikely due to low solubility.

#### 13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products:

Product name: Lube 2000

**PAGE:** 3 of 3

**PRINT DATE: 31/07/2002** 

**REF:** T17

**Contaminated packaging:** Empty containers can be landfilled after cleaning, when in

compliance with local regulations.

**European waste Catalogue No:** 08 04 99

14. TRANSPORT INFORMATION

Proper shipping name: Aerosol

**UN-No:** 1950

ADR/RID Class: 2

**HI/UN No:** 1950

IMO Class: 2

**Proper shipping name:** Aerosol

ICAO Class: 2 UN/ID No: 1950

Proper shipping name Aerosol

### 15. REGULATORY INFORMATION

Classification according to European directive on classification of hazardous preparations 93/21/EEC

- Contains: BUTANE , PROPANE.

- Symbol(s):



Extremely flammable

**R -phrase(s):** R12 - Extremely flammable.

S -phrase(s): S2 - Keep out of reach of children. S16 - Keep away from sources of ignition - No

smoking. S23 - Do not breathe vapour. S51 - Use only in well ventilated areas.

# 16. OTHER INFORMATION

#### Recommended use:

## **Recommended restrictions:**

When used in a mixture, read the labels and safety data sheets of all components.

Revision date: 11/07/2002

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication